


ThermoThin Hook-Up Wire

Smaller. Lighter. Tougher.



Alpha Wire's updated version of the popular ThermoThin line combines maximum performance in an exceptionally small and lightweight construction. ThermoThin is most suited for use in oil and gas, semiconductor, industrial and military industries.

Extreme Temperature Resistance

ThermoThin is uniquely designed to withstand temperatures from -150°C to +300°C to tackle your most demanding applications.

Space-Saving Construction

Up to 35% smaller in diameter than PTFE options, ThermoThin offers an ideal solution when space is at a premium.

Environmental Resistance

Excellent sun, water and chemical resistance ensures consistent performance even when these hazards are present.

Specifications

Temperature Range

-150°C to +300°C

Voltage

600V

Colors

Black
Orange
White
Yellow
Brown
Red
Blue
Green

Additional Colors Available

AWG

16 – 36 AWG

Lengths

Available in continuous lengths of 100 and 1000ft

Approvals and Ratings

UL AWM 11905 (30 AWG and Larger)
Sunlight Resistant
Chemical Resistant
Water Resistant
RoHS and REACH Compliant

Materials

Nickel-plated copper conductor
PFA insulation

Specifications

Part No.	Wire Size		Stranding		Insulation Thickness		Outer Diameter	
	AWG	mm ²	AWG	mm ²	in	mm	in	mm
2636	36	0.013	Solid		0.006	0.15	0.017	0.430
2634	34	0.020	Solid		0.006	0.15	0.018	0.460
2632	32	0.032	Solid		0.006	0.15	0.020	0.510
2630	30	0.057	7/38	7/0.102	0.006	0.15	0.024	0.610
2628	28	0.089	7/36	7/0.127	0.006	0.15	0.027	0.690
2626	26	0.154	19/38	19/0.102	0.007	0.18	0.033	0.840
2624	24	0.241	19/36	19/0.127	0.007	0.18	0.038	0.970
2622	22	0.382	19/34	19/0.16	0.007	0.18	0.044	1.120
2620	20	0.616	19/32	19/0.203	0.007	0.18	0.052	1.320
2618	18	0.963	19/30	19/0.254	0.007	0.18	0.061	1.550
2616	16	1.320	19/0.0117	19/0.297	0.007	0.18	0.070	1.780

600V 28 AWG Comparison



PTFE

OD: 0.035"

Insulation Thickness: 0.010"



ThermoThin

OD: 0.027"

Insulation Thickness: 0.006"



Interested in learning more?

Visit www.alphawire.com/Products/ThermoThin
or call **1-800-52-ALPHA**

The cables you trust. The service you deserve.

Global Headquarters

711 Lidgerwood Avenue
Elizabeth, NJ 07202 | USA
Toll Free: 1-800-52 ALPHA
Tel: 1-908-925-8000
Fax: 1-908-925-5411

Europe

Saxon House
1 Downside | Sunbury-on-Thames
Middlesex | United Kingdom | TW16 6RT
Tel: +44 (0) 1 932 772 422
E-mail: europa@alphawire.com

Asia Pacific

Baohua Mansion | Room 1308
No 1211 Changde Road
Shanghai | China | 200060
Tel: +86-21-6259 3510 / 6259 3957
E-mail: apac@alphawire.com